

# Unit-2. Electrostatics - Medium Solutions

## Part A: Definitions (1-2 marks)

### Electric Field (E)

**Definition:** Electric field at a point is the force experienced by a unit positive charge placed at that point.

**Mathematical Form:**

$$E = F/q_0$$

$$E = kQ/r^2 \text{ (for point charge)}$$

**Units:** N/C or V/m

**Properties:**

- Vector quantity (has magnitude and direction)
- Direction: Away from +ve charge, towards -ve charge
- Exists around any charge




Figure: Electric field lines around charges

### Electric Potential (V)

**Definition:** Electric potential at a point is the work done in bringing a unit positive charge from infinity to that point against the electric field.

**Formula:**

$$V = W/q = kQ/r$$

**Unit:** Volt (V) = Joule/Coulomb (J/C)

**Key Points:**

- Scalar quantity (no direction)
- Reference point:  $V = 0$  at infinity
- $V$  decreases as distance increases
- $V$  is positive around +ve charge, negative around -ve charge

## Electric Potential Difference ( $\Delta V$ )

**Definition:** Work done in moving a unit positive charge from one point to another in an electric field.

**Formula:**

$$\Delta V = V_2 - V_1 = W/q$$

$$W = q(V_2 - V_1)$$

**Unit:** Volt (V)

**Physical Meaning:**

- Measures energy required to move charge
- Battery provides potential difference
- Higher  $\Delta V \rightarrow$  More energy available

## Electric Flux ( $\Phi$ )

**Definition:** Electric flux through a surface is the total number of electric field lines passing through that surface.




Fig. 2.9 : Electric Flux Passing Through Different Surfaces

Figure: Electric flux through a surface

**Formula:**

$$\Phi = E \cdot A = EA \cos \theta$$

Where:

- E = Electric field
- A = Area of surface
- $\theta$  = Angle between E and normal to surface

**Unit:** N·m<sup>2</sup>/C or V·m

**Maximum flux:** When  $\theta = 0^\circ$  (field perpendicular to surface)

**Zero flux:** When  $\theta = 90^\circ$  (field parallel to surface)

## Capacitor

**Definition:** A device consisting of two conductors (plates) separated by an insulator (dielectric), used to store electric charge and energy.

**Basic Structure:**

- Two parallel conducting plates
- Separated by dielectric material (air, mica, ceramic)
- One plate holds  $+Q$ , other holds  $-Q$

**Function:** Stores electrical energy in the electric field between plates

## Capacitance (C)

**Definition:** Capacitance is the ability of a conductor or capacitor to store electric charge. It's the ratio of charge stored to potential difference.

**Formula:**

$$C = Q/V$$

For parallel plate:

$$C = \epsilon_0 \epsilon_r A/d = \epsilon_0 K A/d$$

Where:

- $\epsilon_0 = 8.85 \times 10^{-12} \text{ F/m}$  (permittivity of free space)
- $\epsilon_r = K = \text{dielectric constant}$
- $A = \text{area of plates}$
- $d = \text{distance between plates}$

**Unit:** Farad (F)

- 1 Farad = 1 Coulomb/Volt
- Practical units:  $\mu\text{F}$  ( $10^{-6}$  F),  $\text{nF}$  ( $10^{-9}$  F),  $\text{pF}$  ( $10^{-12}$  F)

## Part B: Detailed Answers (2-3 marks)

### (1) State and explain Coulomb's law

**Statement:** The force of attraction or repulsion between two stationary point charges is directly proportional to the product of the charges and inversely proportional to the square of the distance between them.

$$F \propto \frac{q_1 q_2}{r^2}$$

$$\therefore F = k \frac{q_1 q_2}{r^2} \quad \dots (3)$$

Figure: Force between two point charges

#### Mathematical Form:

$$F \propto q_1 q_2 \quad \text{and} \quad F \propto 1/r^2$$

$$\text{Therefore: } F = k(q_1 q_2)/r^2$$

Where:

- $k = 9 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$  (Coulomb's constant)
- $k = 1/(4\pi\epsilon_0)$
- $\epsilon_0 = 8.85 \times 10^{-12} \text{ F/m}$

## Vector Form:

$$\vec{F} = k(q_1 q_2 / r^2) \hat{r}$$

## Nature of Force:

- **Like charges** (both +ve or both -ve): **Repulsive** (push apart)
- **Unlike charges** (+ve and -ve): **Attractive** (pull together)

## Key Points:

- Valid for point charges or spherical charge distributions
- Force acts along the line joining the charges
- Obeys Newton's third law (action-reaction pair)

## (2) Draw and explain characteristics of electric field lines

**Electric Field Lines:** Imaginary lines whose tangent at any point gives the direction of electric field at that point.




Figure: Electric field line patterns for different charge configurations

## Characteristics:

1. **Origin and Termination:**
  - Start from positive charges (or infinity)
  - End at negative charges (or infinity)
2. **Direction:**
  - Tangent to field line gives direction of electric field
  - Arrow shows direction of force on +ve test charge
3. **No Intersection:**
  - Two field lines never cross each other

- If they crossed, field would have two directions at that point (impossible)

#### 4. Density indicates strength:

- Closely spaced lines → Strong field
- Widely spaced lines → Weak field
- Number of lines  $\propto$  magnitude of charge

#### 5. Uniform field:

- Parallel and equally spaced lines
- Example: Between two parallel charged plates

#### 6. Imaginary nature:

- Lines are visualization tool, not physical entities
- Electric field is real and exists everywhere

#### 7. Perpendicular to surface:


- Field lines always meet conductor surface perpendicularly
- Tangential component = 0 on conductor surface

#### 8. Open curves:

- Electrostatic field lines never form closed loops
- They have definite starting and ending points

## (3) Parallel plate capacitor - construction, capacitance, factors

### Construction:



**Fig. 2.4 The electric field of a set of charges**

Figure: Structure of parallel plate capacitor

- Two parallel conducting plates of equal area A
- Separated by distance d
- Dielectric material (air, mica, ceramic) between plates
- One plate connected to +ve terminal (charge +Q)
- Other plate connected to -ve terminal (charge -Q)

#### Capacitance Formula:

$$C = \epsilon_0 \epsilon_r A/d = \epsilon_0 K A/d$$

Where:

$$\epsilon_0 = 8.85 \times 10^{-12} \text{ F/m}$$

$\epsilon_r$  = K = relative permittivity (dielectric constant)

A = area of plates ( $\text{m}^2$ )

d = separation between plates (m)

#### Factors Affecting Capacitance:

##### 1. Area of plates (A):

- $C \propto A$
- Larger area → More charge storage → Higher capacitance

##### 2. Distance between plates (d):

- $C \propto 1/d$
- Smaller distance → Stronger field → Higher capacitance

### 3. Dielectric constant (K):

- $C \propto K$
- Higher K → More capacitance
- Air: K=1, Mica: K≈6, Ceramic: K≈1000

### 4. Permittivity of free space ( $\epsilon_0$ ):

- Fundamental constant =  $8.85 \times 10^{-12} \text{ F/m}$

### Applications:

- Tuning circuits, filters, energy storage
- Power supply smoothing, coupling/decoupling
- Flash photography, timing circuits

## (4) Series combination of capacitors

**Configuration:** Capacitors connected end-to-end (negative of one to positive of next)




Figure: Capacitors in series connection

### Characteristics:

#### 1. Same charge on all capacitors:

$$Q_1 = Q_2 = Q_3 = Q \text{ (constant)}$$

#### 2. Voltage divides:

$$V = V_1 + V_2 + V_3$$

#### 3. Individual voltages:

$$V_1 = Q/C_1, \quad V_2 = Q/C_2, \quad V_3 = Q/C_3$$

## Derivation:

$$V = V_1 + V_2 + V_3$$

$$Q/C_s = Q/C_1 + Q/C_2 + Q/C_3$$

Dividing by  $Q$ :

$$1/C_s = 1/C_1 + 1/C_2 + 1/C_3$$

## Special Cases:

Two capacitors:  $C_s = (C_1 C_2) / (C_1 + C_2)$

$n$  equal capacitors:  $C_s = C/n$

**Key Point:** Equivalent capacitance is **less than smallest** individual capacitance

**Application:** To reduce effective capacitance and increase voltage rating

## (5) Parallel combination of capacitors

**Configuration:** All capacitors connected to same two points (all +ve terminals together, all -ve terminals together)




Figure: Capacitors in parallel connection

### Characteristics:

1. **Same voltage across all capacitors:**

$$V_1 = V_2 = V_3 = V \text{ (constant)}$$

2. **Charge divides:**

$$Q = Q_1 + Q_2 + Q_3$$

### 3. Individual charges:

$$Q_1 = C_1 V, \quad Q_2 = C_2 V, \quad Q_3 = C_3 V$$

#### Derivation:

$$Q = Q_1 + Q_2 + Q_3$$

$$C_p V = C_1 V + C_2 V + C_3 V$$

Dividing by V:

$$C_p = C_1 + C_2 + C_3$$

#### Special Case:

$$n \text{ equal capacitors: } C_p = nC$$

**Key Point:** Equivalent capacitance is **greater than largest** individual capacitance

**Application:** To increase effective capacitance and charge storage

## (6) Effect of dielectric on capacitance of capacitor

**Dielectric:** Insulating material (glass, mica, ceramic, paper) placed between capacitor plates




Figure: Effect of dielectric on capacitor

**Effect: Capacitance Increases**

$$C = KC_0$$

Where:

C<sub>0</sub> = capacitance with air/vacuum

K = dielectric constant ( $\epsilon_r$ )

K > 1 for all materials

### Why Capacitance Increases:

1. **Polarization:** Dielectric molecules align with electric field
  - o +ve ends toward -ve plate
  - o -ve ends toward +ve plate
2. **Reduced field:** Internal field opposes applied field

$$E = E_0 / K$$

3. **Reduced voltage:** For same charge  $Q$

$$V = V_0 / K$$

4. **Increased capacitance:**  $C = Q/V$

$$C = Q / (V_0 / K) = K(Q/V_0) = KC_0$$

### Other Effects:

1. **Increases breakdown voltage:** Can apply higher voltage without sparking
2. **Mechanical support:** Keeps plates separated uniformly
3. **Compact design:** Higher  $C$  in smaller size

### Common Dielectrics:

Material	K (Dielectric Constant)
Vacuum	1.0000
Air	1.0006
Paper	3.7
Glass	5-10
Mica	6
Ceramic	100-1000

## Part C: Numerical Problems (3 marks)

### (1) Force between two charges (Coulomb's law)

Given:

- $q_1 = 20 \mu C = 20 \times 10^{-6} C$
- $q_2 = 10 \mu C = 10 \times 10^{-6} C$

- $r = 0.02 \text{ m} = 2 \text{ cm}$
- $k = 9 \times 10^9 \text{ N}\cdot\text{m}^2/\text{C}^2$

**Formula:**

$$F = kq_1q_2/r^2$$

**Calculation:**

$$F = (9 \times 10^9) \times (20 \times 10^{-6}) \times (10 \times 10^{-6}) / (0.02)^2$$

$$F = (9 \times 10^9) \times (200 \times 10^{-12}) / (4 \times 10^{-4})$$

$$F = 1800 \times 10^{-3} / 4 \times 10^{-4}$$

$$F = 1.8 / (4 \times 10^{-4}) = 4500 \text{ N}$$

**Answer:  $F = 4500 \text{ N}$  (repulsive force, both charges positive)**

## (2) Potential difference from work done

**Given:**

- $W = 1600 \text{ J}$
- $q = 25 \text{ C}$

**Formula:**

$$V = W/q$$

**Calculation:**

$$V = 1600/25 = 64 \text{ V}$$

**Answer:  $V = 64 \text{ V}$**

**Interpretation:** 64 joules of work is required to move 1 coulomb of charge between the two points.

## (3) Capacitance from charge and voltage

**Given:**

- $Q = 60 \mu\text{C} = 60 \times 10^{-6} \text{ C}$
- $V = 12 \text{ V}$

**Formula:**

$$C = Q/V$$

**Calculation:**

$$C = (60 \times 10^{-6}) / 12 = 5 \times 10^{-6} \text{ F} = 5 \text{ } \mu\text{F}$$

**Answer:**  $C = 5 \mu\text{F}$

## (4) Three $10\mu\text{F}$ capacitors in series and parallel

**Given:**  $C_1 = C_2 = C_3 = 10 \mu\text{F}$

**Series Connection:**

For  $n$  equal capacitors:  $C_s = C/n$

$$C_s = 10/3 = 3.33 \text{ } \mu\text{F}$$

**Parallel Connection:**

For  $n$  equal capacitors:  $C_p = nC$

$$C_p = 3 \times 10 = 30 \text{ } \mu\text{F}$$

**Answers:**

- **Series:**  $C_s = 3.33 \mu\text{F}$
- **Parallel:**  $C_p = 30 \mu\text{F}$

**Comparison:** Parallel gives 9 times more capacitance than series for same capacitors!

## (5) Capacitance of small capacitor

**Given:**

- $A = 10 \text{ mm}^2 = 10 \times 10^{-6} \text{ m}^2 = 10^{-5} \text{ m}^2$
- $d = 1 \text{ mm} = 1 \times 10^{-3} \text{ m}$
- $\epsilon_0 = 8.85 \times 10^{-12} \text{ F/m}$
- Air dielectric ( $K = 1$ )

**Formula:**

$$C = \epsilon_0 A/d$$

**Calculation:**

$$C = (8.85 \times 10^{-12}) \times (10^{-5}) / (10^{-3})$$

$$C = 8.85 \times 10^{-17} / 10^{-3}$$

$$C = 8.85 \times 10^{-14} \text{ F} = 0.0885 \text{ pF}$$

**Answer:**  $C = 8.85 \times 10^{-14} \text{ F}$  (or  $0.0885 \text{ pF}$ )

**Note:** Very small capacitance due to small area!

## (6) Area required for 1 Farad capacitor

**Given:**

- $C = 1 \text{ F}$
- $d = 1 \text{ mm} = 10^{-3} \text{ m}$
- $\epsilon_0 = 8.85 \times 10^{-12} \text{ F/m}$

**Formula:**

$$C = \epsilon_0 A/d \rightarrow A = Cd/\epsilon_0$$

**Calculation:**

$$A = (1) \times (10^{-3}) / (8.85 \times 10^{-12})$$

$$A = 10^{-3} / 8.85 \times 10^{-12}$$

$$A = 1.13 \times 10^8 \text{ m}^2$$

**Converting to km<sup>2</sup>:**

$$A = 1.13 \times 10^8 \text{ m}^2 = 113 \text{ km}^2$$

**Answer:**  $A = 1.13 \times 10^8 \text{ m}^2$  (113 km<sup>2</sup>)

**Interpretation:** This shows 1 Farad is an enormous capacitance! That's why we use  $\mu\text{F}$ ,  $\text{nF}$ ,  $\text{pF}$  in practice. Area needed is larger than a small city!

## (7) Mixed circuit (series-parallel combination)

**Problem:** Find equivalent capacitance when  $C_1$  and  $C_2$  are in parallel, and this combination is in series with  $C_3$ .

**Given:**

- $C_1 = 10 \mu\text{F}$

- $C_2 = 20 \mu F$
- $C_3 = 30 \mu F$
- Configuration:  $(C_1 \parallel C_2)$  in series with  $C_3$

### Step 1: Parallel combination of $C_1$ and $C_2$

$$C_{12} = C_1 + C_2 = 10 + 20 = 30 \mu F$$

### Step 2: Series combination with $C_3$

$$1/C_t = 1/C_{12} + 1/C_3$$

$$1/C_t = 1/30 + 1/30 = 2/30$$

$$C_t = 30/2 = 15 \mu F$$

**Answer: Total capacitance = 15  $\mu F$**

**Alternative method (for two equal capacitors in series):**

$$C_t = (C_{12} \times C_3) / (C_{12} + C_3) = (30 \times 30) / (30 + 30) = 900/60 = 15 \mu F$$

## Quick Reference

### Essential Formulas

Coulomb's Law:  $F = kq_1q_2/r^2$ ,  $k = 9 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$

Electric Field:  $E = F/q = kQ/r^2$

Electric Potential:  $V = W/q = kQ/r$

Potential Difference:  $\Delta V = V_2 - V_1 = W/q$

Electric Flux:  $\Phi = EA \cos \theta$

Capacitance:  $C = Q/V$

Parallel Plate:  $C = \epsilon_0 \epsilon_r A/d = \epsilon_0 K A/d$

Series:  $1/C_s = 1/C_1 + 1/C_2 + 1/C_3$

Parallel:  $C_p = C_1 + C_2 + C_3$

Dielectric effect:  $C = KC_0$

Energy stored:  $U = \frac{1}{2}QV = \frac{1}{2}CV^2 = Q^2/(2C)$

## Important Constants

$k$  (Coulomb's constant) =  $9 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$

$\epsilon_0$  (Permittivity of free space) =  $8.85 \times 10^{-12} \text{ F/m}$

$e$  (Electron charge) =  $1.6 \times 10^{-19} \text{ C}$

$1 \mu F = 10^{-6} \text{ F}$

$1 \text{ nF} = 10^{-9} \text{ F}$

$1 \text{ pF} = 10^{-12} \text{ F}$

